

# Mobil 1 Synthetic Gear Lubricant LS 75W-140

## Supreme Performance Synthetic Multi-Purpose Automotive Gear Lubricant

### Product Description

Mobil 1 Synthetic Gear Lubricant LS 75W-140 is a supreme performance, synthetic, multi-purpose, automotive gear lubricant designed to meet the highest level performance requirements of many modern passenger vehicles in all types of operating conditions including limited slip applications, as well as deliver outstanding power transfer performance. Compared to conventional hypoid gear lubricants, Mobil 1 Synthetic Gear Lubricant LS 75W-140 performs exceptionally over a wide range of temperatures. Mobil 1 Synthetic Gear Lubricant LS 75W-140 achieves this through a unique proprietary combination of synthetic baseoils and a unique additive system including the SuperSyn antiwear system., that deliver optimized viscosity-temperature properties together with the highest level of inherent formulation stability and protects against thermal and oxidative degradation, wear and corrosion, viscosity loss associated with premature shearing.

Mobil 1 Synthetic Gear Lubricant LS 75W-140 meets the API Service GL-5 EP gear oil service classification.

### Features and Benefits

Mobil 1 Synthetic Gear Lubricant LS 75W-140 combines wax-free synthesized hydrocarbon base oils and a specially designed extreme-pressure, limited-slip, sulfur-phosphorous additive system including the SuperSyn antiwear technology to provide a significantly higher level of performance in rear axles and differentials versus conventional fluids. Greater film strength at higher operating temperatures, reduced fluid friction and significant advantages versus conventional mineral oil formulations. It reduces wear and spalling under the high speed, high torque and high horsepower conditions in many sport utility vehicles , vans, light trucks , and cars. This unique, high technology final drive gear lubricant has demonstrated outstanding performance including long-term friction retention, excellent viscosity stability and improved differential/axle durability and cleanliness. Key features and benefits include:

Features	Advantages and Potential Benefits
Exceptional thermal stability and resistance to high temperature oxidation	Extended gear and bearing life due to minimal deposits Longer seal life Potential extended oil drain/service intervals
Outstanding protection against low speed/high torque wear and against high speed scoring	Capability to handle the severest driving conditions while delivering smooth efficient and reliable performance
Exceptional shear stability	Retains viscosity and film strength under severe operating conditions to prevent wear
Excellent rust, staining and corrosion protection of copper and its alloys	Reduced wear Longer component life
Enhanced frictional properties	Improved fuel economy and reduced operating costs
Outstanding low temperature fluidity versus mineral oils	Reduced wear at start up and ease of start up even in arctic conditions
Good resistance to foaming	Maintains film strength for reliable lubrication



Features	Advantages and Potential Benefits
Compatible with typical automotive seals and gaskets	Minimum leakage and reduced contamination
Excellent limited-slip performance	Reduced chatter and improved traction

## Applications

- Mobil 1 Synthetic Gear Lubricant LS 75W-140 is recommended for use in modern high performance vehicles like sport utility vehicles , vans and light duty trucks requiring API GL-5 performance that require excellent durability
- Mobil 1 Synthetic Gear Lubricant LS 75W-140 is intended for initial fill, topping-off or refilling differentials, final drives, transfer cases and other gear applications where lubricants meeting API Service GL-5 and multi-purpose or mild EP gear lubricants are recommended
- Mobil 1 Synthetic Gear Lubricant LS 75W-140 can also be used in rear axles where API Service GL-4 lubricant is recommended
- Not recommended for automatic, manual or semiautomatic transmissions for which engine oil or automatic transmission fluids are recommended
- Recommended for many limited slip applications. For certain high level LS applications, additional limited slip additive may be required if axle chatter is observed.

## Specifications and Approvals

Mobil 1 Synthetic Gear Lubricant LS meets or exceeds the following industry specifications:	75W-140
API GL-5	X

## Typical Properties

Mobil 1 Synthetic Gear Lubricant LS	
SAE Grade	75W-140
Viscosity, ASTM D 445	
cSt @ 40°C	179
cst @ 100°C	25.3
Viscosity Index, ASTM D 2270	175
Pour Point, °C, ASTM D 97	-51
Flash Point, °C, ASTM D 92	221
Density @ 15°C kg/l, ASTM D 4052	0.863

## Health and Safety

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application and the recommendations provided in the Material Safety Data Sheet (MSDS) are followed. MSDS's are available upon request through your sales contract office, or via the Internet. This product should not be used for purposes other than its intended use. If disposing of used product, take care to protect the environment.



*The Mobil logotype, the Pegasus design, Mobil 1 Gear Lubricant are trademarks of Exxon Mobil Corporation, or one of its subsidiaries.*

ExxonMobil Lubricants & Specialties  
All products may not be available locally. For more information, contact your local sales office or visit [www.exxonmobil.com](http://www.exxonmobil.com).  
ExxonMobil is comprised of numerous affiliates and subsidiaries, many with names that include Esso, Mobil, or ExxonMobil. Nothing in this document is intended to override or supersede the corporate separateness of local entities. Responsibility for local action and accountability remains with the local ExxonMobil affiliate entities. Due to continual product research and development, the information contained herein is subject to change without notification. Typical Properties may vary slightly.  
© 2007 Exxon Mobil Corporation. All rights reserved.